

B1

Spiral Wrap

B2



B3

- Harness multiple cables into a single manageable bundle
- Allows breakouts of single/multiple cables
- Provides abrasion protection for wire, cables, hoses, and tubing
- Reverse cut
- Multiple colors allow easy identification of cable bundles
- Installation tool supplied in each package
- Available in multiple materials
- Reusable
- UL File: E141152
- Voltage Rating: 600 V

C1

C2

C3

C4

D1

D2

D3

E1

E2

E3

E4

E5

F

G

H

Part Number	Material*	Color	Length Per Reel‡		Bundle Diameter Range		Outside Diameter		Temperature Range	Wall Thickness		Std. Pkg. Qty.
			Ft.	m	In.	mm	In.	mm		In.	mm	
T12F-C	Polyethylene	Natural	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-40°F – 122°F (-40°C – 50°C)	0.030	0.76	1
T12F-D			500	152.4	1/16 – 1/2	1.6 – 12.7	0.12	3.2		0.030	0.76	
T19F-C			100	30.5	1/8 – 1	3.2 – 25.4	0.19	4.8		0.035	0.89	
T19F-M			1,000	304.8	1/8 – 1	3.2 – 25.4	0.19	4.8		0.035	0.89	
T25F-C	Polyethylene	Natural	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4	-40°F – 122°F (-40°C – 50°C)	0.040	1.02	
T25F-C1	Polyethylene	Brown	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C2		Red	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C3Y		Orange	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C4Y		Yellow	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C5		Green	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C6		Blue	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C7		Purple	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C8		Gray	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C10		White	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C16		Pink	100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-M	Polyethylene	Natural	1,000	304.8	3/16 – 2	4.8 – 50.8	0.25	6.4	-40°F – 122°F (-40°C – 50°C)	0.040	1.02	
T38F-C			100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T38F-TL			250	76.2	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T50F-X			10	3.1	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C	Polyethylene	Natural	100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7	-40°F – 122°F (-40°C – 50°C)	0.060	1.52	
T50F-C1			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C2			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C3Y			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C4Y			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C5			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C6			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C7			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C8			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C10			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C16	Polyethylene	Natural	100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7	-40°F – 122°F (-40°C – 50°C)	0.060	1.52	
T50F-TL			250	76.2	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-TL4Y			250	76.2	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T62F-C			100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9	-40°F – 122°F (-40°C – 50°C)	0.062	1.57	
T62F-TL	Polyethylene	Natural	250	76.2	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.062	1.57	
T75F-C			100	30.5	5/8 – 5	15.9 – 127.0	0.75	19.1		0.065	1.65	
T75F-T			200	61.0	5/8 – 5	15.9 – 127.0	0.75	19.1		0.065	1.65	
T100F-C			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.070	1.78	

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Spiral Wrap (continued)

			Length Per Reel†		Bundle Diameter Range		Outside Diameter			Wall Thickness		Std. Pkg. Qty.
Part Number	Material*	Color	Ft.	m	In.	mm	In.	mm	Temperature Range	In.	mm	
T12F-C0	Weather Resistant Polyethylene	Black	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-40°F – 122°F (-40°C – 50°C)	0.030	0.76	1
T12F-D0			500	152.4	1/16 – 1/2	1.6 – 12.7	0.12	3.2		0.030	0.76	
T19F-C0			100	30.5	1/8 – 1	3.2 – 25.4	0.19	4.8		0.035	0.89	
T25F-X0			10	3.1	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-C0			100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25F-M0			1,000	304.8	3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T38F-C0			100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T38F-TL0			250	76.2	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T50F-X0			10	3.1	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-C0			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50F-TL0			250	76.2	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T62F-C0	Weather Resistant Polyethylene	Black	100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9	-40°F – 122°F (-40°C – 50°C)	0.062	1.57	1
T62F-TL0			250	76.2								
T75F-C0			100	30.5	5/8 – 5	15.9 – 127.0	0.75	19.1		0.065	1.65	
T75F-T0			200	61.0								
T100F-C0			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.070	1.78	
T12R-CY	Fire Resistant Polyethylene	Natural	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-40°F – 122°F (-40°C – 50°C)	0.030	0.76	1
T19R-CY					1/8 – 1	3.2 – 25.4	0.19	4.8		0.035	0.89	
T25R-CY					3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25R-C20Y		Black										
T25R-MY		Natural	1,000	304.8	3/16 – 2	4.8 – 50.8	0.25	6.4				
T25R-M20Y		Black										
T38R-CY		Natural	100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T38R-TLY			250	76.2								
T50R-CY			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50R-TLY			250	76.2								
T62R-CY		Natural	100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.062	1.57	
T75R-CY					5/8 – 5	15.9 – 127.0	0.75	19.1		0.065	1.65	
T100R-CY					7/8 – 6	22.2 – 152.4	1.00	25.4		0.070	1.78	
T12FR-CY	Flame Retardant Polyethylene	Natural	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-4°F – 122°F (-20°C – 50°C)	0.030	0.76	1
T12FR-C20Y		Black										
T19FR-CY		Natural			1/8 – 1	3.2 – 25.4	0.19	4.8		0.032	0.80	
T19FR-C20Y		Black										
T25FR-CY		Natural			3/16 – 2	4.8 – 50.8	0.25	6.4		0.040	1.02	
T25FR-C20Y		Black										
T25FR-MY	Flame Retardant Polyethylene	Natural	1,000	304.8	3/16 – 2	4.8 – 50.8	0.25	6.4	-4°F – 122°F (-20°C – 50°C)	0.040	1.02	1
T25FR-M20Y		Black										
T38FR-CY		Natural	100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.055	1.40	
T38FR-C20Y		Black										
T38FR-TLY		250	76.2									
T50FR-CY		Natural	100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.060	1.52	
T50FR-C20Y		Black	250	76.2								
T50FR-TLY		Natural										
T62FR-CY		Black	100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.062	1.57	
T62FR-C20Y												
T75FR-CY		Natural			5/8 – 5	15.9 – 127.0	0.75	19.1		0.065	1.65	
T75FR-C20Y		Black										
T75FR-TY												
T100FR-CY		Natural	200	61.0								
T100FR-C20Y		Black	100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.070	1.78	

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

†Reel packaging may contain splices. Contact Panduit Customer Service for further information.

Continued on next page

Spiral Wrap (continued)

		Color	Length Per Reel‡		Bundle Diameter Range		Outside Diameter			Wall Thickness		Std. Pkg. Qty.
Part Number	Material*		Ft.	m	In.	mm	In.	mm	Temperature Range	In.	mm	
T12N-C	Nylon 6.6	Natural	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-40°F – 149°F (-40°C – 65°C)	0.015	0.38	1
T12N-D			500	152.4								
T19N-C			100	30.5	1/8 – 1	3.2 – 25.4	0.19	4.8		0.020	0.51	
T19N-M			1,000	304.8								
T25N-C			100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.023	0.58	
T25N-M			1,000	304.8								
T38N-C			100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.030	0.76	
T38N-TL			250	76.2		5/16 – 3						
T50N-C	Nylon 6.6	Natural	100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7	-40°F – 149°F (-40°C – 65°C)	0.032	0.81	1
T50N-TL			250	76.2	3/8 – 4	9.5 – 101.6	0.50	12.7		0.032	0.81	
T62N-C			100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.035	0.89	
T75N-C			100	30.5	5/8 – 5	15.9 – 127.0	0.75	19.1		0.040	1.02	
T75N-T			200	61	5/8 – 5	15.9 – 127.0	0.75	19.1		0.040	1.02	
T100N-C			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.045	1.14	
T12N-C0	Weather Resistant Nylon 6.6	Black	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-40°F – 149°F (-40°C – 65°C)	0.015	0.38	1
T19N-C0			100	30.5	1/8 – 1	3.2 – 25.4	0.19	4.8		0.020	0.51	
T19N-M0			1,000	304.8	1/8 – 1	3.2 – 25.4	0.19	4.8		0.020	0.51	
T25N-M0			1,000	304.8	3/16 – 2	4.8 – 50.8	0.25	6.4		0.023	0.58	
T25N-C0			100	30.5	3/16 – 2	4.8 – 50.8	0.25	6.4		0.023	0.58	
T38N-C0			100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5		0.030	0.76	
T50N-C0			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.032	0.81	
T50N-TL0			250	76.2	3/8 – 4	9.5 – 101.6	0.50	12.7		0.032	0.81	
T62N-C0			100	30.5	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.035	0.89	
T75N-C0			100	30.5	5/8 – 5	15.9 – 127.0	0.75	19.1		0.040	1.02	
T100N-C0			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.045	1.14	
T25NZFR-C20			Low Smoke Halogen-Free Flame Retardant Nylon 6	Black	100	30.5	3/16 – 2	4.8 – 50.8		0.25	6.4	
T38NZFR-C20	100	30.5			5/16 – 3	7.9 – 76.2	0.38	9.5	0.030	0.76		
T50NZFR-C20	100	30.5			3/8 – 4	9.5 – 101.6	0.50	12.7	0.032	0.81		
T75NZFR-C20	Low Smoke Halogen-Free Flame Retardant Nylon 6	Black	100	30.5	5/8 – 5	15.9 – 127.0	0.75	19.1	-40°F – 149°F (-40°C – 65°C)	0.040	1.02	1
T100NZFR-C20			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4	-40°F – 239°F (-40°C – 115°C)	0.030	0.76	
T38P-C0	Weather Resistant Polypropylene	Black	100	30.5	5/16 – 3	7.9 – 76.2	0.38	9.5	-40°F – 239°F (-40°C – 115°C)	0.030	0.76	1
T50P-C0			100	30.5	3/8 – 4	9.5 – 101.6	0.50	12.7		0.030	0.76	
T100P-C0			100	30.5	7/8 – 6	22.2 – 152.4	1.00	25.4		0.030	0.76	
T12T-C	TFE^	Natural	100	30.5	1/16 – 1/2	1.6 – 12.7	0.12	3.2	-454°F – 356°F (-270°C – 180°C)	0.020	0.51	1
T19T-C			100	30.5	1/8 – 1	3.2 – 25.4	0.19	4.8		0.030	0.76	
T25T-L	50	15.2	3/16 – 2	4.8 – 50.8	0.25	6.4	0.030	0.76				
T25T-L0	TFE^	Black	50	15.2	3/16 – 2	4.8 – 50.8	0.25	6.4		0.030	0.76	
T38T-L	TFE^	Natural	50	15.2	5/16 – 3	7.9 – 76.2	0.38	9.5		0.030	0.76	
T50T-Q			25	7.6	3/8 – 4	9.5 – 101.6	0.50	12.7		0.030	0.76	
T62T-Q			25	7.6	1/2 – 4 1/2	12.7 – 114.3	0.62	15.9		0.030	0.76	
T75T-X			10	3.1	5/8 – 5	15.9 – 127.0	0.75	19.1		0.030	0.76	
T100T-X			10	3.1	7/8 – 6	22.2 – 152.4	1.00	25.4		0.040	1.02	

*Flame retardant products are manufactured from a material that is rated UL 94V-0.

‡Reel packaging may contain splices. Contact Panduit Customer Service for further information

^TFE is Polytetrafluorethylene material.