

Two-Piece Deep Junction Box, Power Rated



- Accepts standard NEMA single gang faceplates
- Single gang two-piece screw together outlet box



JBP1DWH

Part Number	Gang Opening Type	Color
JBP1DWH	Single Gang	White

Pan-Ty® Locking Cable Tie

- Versatile cable ties can be used in multiple applications
- One-piece locking wedge for consistent performance, low thread force, and high loop tensile strength
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easier to pick up from flat surfaces and allows faster initial threading during installation (SM, M, I, S cross sections only)
- A variety of materials and colors are available for specific applications, visit panduit.com
- UL Listed for use in AH-2 air handling places (select part numbers - visit UL site for further details)



PLT.6SM-C



PLT.6SM-M0



PLT.6SM-M30



PLT.7M-M



PLT.7M-M0

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLT.6SM-C	0.6 (15)	2.8 (71)	0.07 (1.8)	8 (36)	Nylon 6.6	Natural	—	100	GTS-E, PTS
PLT.6SM-M0						Black	UV-Resistant, Weather-Resistant	1000	
PLT.6SM-M30							Heat-Resistant		
PLT.7M-M	0.68 (17)	3.1 (79)	0.09 (2.3)	18 (80)		Natural	—	1000	GTS-E, GS2B-E, PTS, PPTS, STS2
PLT.7M-M0						Black	UV-Resistant, Weather-Resistant		
PLT1.5I-C						1.38 (35)	5.6 (142)	0.142 (3.6)	
PLT1.5I-C0	Black	UV-Resistant, Weather-Resistant							
PLT1.5I-C6120		Chemical-Resistant, UV-Resistant, Weather-Resistant	GTS-E, GS2B-E, PTS, PTH, PPTS, STS2						
PLT1.5I-M	Nylon 6.6	Natural	—	1000	GTS-E, GS2B-E, PTS, PPTS, STS2				
PLT1.5I-M0		Black	UV-Resistant, Weather-Resistant						
PLT1.5I-M00		Black	UV-Resistant, Weather-Resistant						1000

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With		
PLT1.5I-M100	1.38 (35)	5.6 (142)	0.142 (3.6)	18 (80)	Polypropylene	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	1000	GTS-E, GS2B-E, PTS, PPTS, STS2		
PLT1.5I-M20				Nylon 6.6	—						
PLT1.5I-M30							Heat-Resistant				
PLT1.5I-M6120			25 (111)	Nylon 612	Chemical-Resistant, UV-Resistant, Weather-Resistant						
PLT1.5M-C	1.25 (32)		0.098 (2.5)	18 (80)	Nylon 6.6	Natural	—	100		GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT1.5M-C0						Black	UV-Resistant, Weather-Resistant				
PLT1.5M-C71	1.38 (35)	5.9 (150)	0.101 (2.6)	35 (156)	PEEK	Translucent Brown	Chemical-Resistant, High Heat-Resistant, Radiation-Resistant				
PLT1.5M-M	1.25 (32)	5.6 (142)	0.098 (2.5)	18 (80)	Nylon 6.6	Natural	—	1000			GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT1.5M-M0						Black	UV-Resistant, Weather-Resistant				
PLT1.5M-M20							—				
PLT1.5M-M30							Heat-Resistant				
PLT1.5S-M	1.5 (38)	6.2 (157)	0.19 (4.8)	50 (222)		Natural	—				
PLT1.5S-M0						Black	UV-Resistant, Weather-Resistant				
PLT10LH-C	10.3 (262)	34.2 (871)	0.3 (7.6)	120 (534)		Nylon 6.6	Natural	—	100		
PLT12EH-C	12 (304.8)	40.1 (1019)	0.5 (12.7)	250 (1112)			Black	UV-Resistant, Weather-Resistant		GS4EH-E, ST3EH	
PLT12EH-C0											
PLT13H-C	13 (330)	43.3 (1100)	0.35 (8.9)	175 (778)			Natural	—	25	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT13H-C0					Black		UV-Resistant, Weather-Resistant				
PLT13H-Q					Natural		—				
PLT13H-Q0					Black		UV-Resistant, Weather-Resistant				
PLT1M-C	0.87 (22)	3.94 (99)	0.098 (2.5)	18 (80)			Natural	—		GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT1M-C0				Black			UV-Resistant, Weather-Resistant				
PLT1M-C186		3.94 (100)		15 (67)	Polypropylene		Dark Blue	Chemical-Resistant		GTS-E, GS2B-E, STS2	
PLT1M-C6120		3.94 (99)		20 (89)	Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, PTS, PTH, PPTS, STH2		
PLT1M-C702Y		4 (102)		18 (80)	ECTFE	Maroon	Heat-Resistant, UV- Resistant, Weather- Resistant		GTS-E, GS2B-E, PTS, PPTS, STS2		
PLT1M-C71				0.101 (2.6)	35 (156)	PEEK	Translucent Brown	Chemical-Resistant, High Heat-Resistant, Radiation-Resistant			
PLT1M-C76		0.87 (22)		4 (102)	0.098 (2.5)	18 (80)	ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, PTS, PPTS, STS2

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With	
PLT1M-C96A	0.87 (22)	3.94 (100)	0.098 (2.5)	18 (80)	Nylon 6.6	Blue	Antimicrobial	100	GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT1M-M		Black				Natural	—	1000		
PLT1M-M0						UV-Resistant, Weather-Resistant				
PLT1M-M00				Chemical-Resistant, UV-Resistant, Weather-Resistant						
PLT1M-M100		—								
PLT1M-M20					Heat-Resistant					
PLT1M-M30				Heat-Resistant, UV- Resistant, Weather- Resistant						
PLT1M-M300		Chemical-Resistant, UV-Resistant, Weather-Resistant								
PLT1M-M6120					Nylon 612					
PLT1M-M69				Nylon 6.6		Ivory	Flame-Retardant			
PLT1M-M702Y		ECTFE		Maroon		Heat-Resistant, UV- Resistant, Weather- Resistant	Black			UV-Resistant, Weather-Resistant
PLT1S-M0	1 (25)	4.8 (122)	0.19 (4.8)	50 (222)	Nylon 6.6	Natural		—	GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT1S-M30	2.5 (64)	9.7 (246)	0.145 (3.7)	40 (178)		Black		Heat-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT2.5I-M							2.5 (64)	9.7 (246)	0.145 (3.7)	
PLT2.5I-M0	2.5 (63.5)	9.8 (249)	0.19 (4.8)	50 (222)		Black	UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	
PLT2.5S-C0							Chemical-Resistant, UV-Resistant, Weather-Resistant			
PLT2.5S-C6120	2.5 (64)					Nylon 612		Black	UV-Resistant, Weather-Resistant	100
PLT2.5S-M	2.5 (63.5)					Nylon 6.6	Natural		—	
PLT2.5S-M0								Nylon 612	Black	UV-Resistant, Weather-Resistant
PLT2.5S-M6120	2.5 (64)					Nylon 612	Chemical-Resistant, UV-Resistant, Weather-Resistant			Black
PLT2H-L0	2 (51)	8.1 (206)	0.3 (7.6)	120 (534)	Nylon 6.6	Chemical-Resistant, UV-Resistant, Weather-Resistant	250			
PLT2H-TL100				50 (222)	Polypropylene	Heat-Resistant				
PLT2H-TL30				120 (534)	Nylon 6.6	Natural	—	100	GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT2I-C	8 (203)	0.142 (3.6)	40 (178)				Black			UV-Resistant, Weather-Resistant
PLT2I-C0										2 (51)

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With	
PLT2I-C30	2 (51)	8 (203)	0.142 (3.6)	40 (178)	Nylon 6.6	Black	Heat-Resistant	100	GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT2I-C76			0.135 (3.4)	30 (133)	ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant			
PLT2I-C96A						Blue	Antimicrobial			GTS-E, GS2B-E, STS2S
PLT2I-M			0.142 (3.6)	40 (178)	Nylon 6.6	Natural	—	1000	GTS-E, GS2B-E, PTS, PPTS, STS2	
PLT2I-M0						Black	UV-Resistant, Weather-Resistant			
PLT2I-M20							—			
PLT2I-M30							Heat-Resistant			
PLT2I-M300							Heat-Resistant, UV- Resistant, Weather- Resistant			
PLT2I-M59						Fluorescent Pink	—	100		
PLT2M-C						Natural				
PLT2M-C0						Black	UV-Resistant, Weather-Resistant	1000		
PLT2M-M						Natural	—			
PLT2M-M0			Black	UV-Resistant, Weather-Resistant						
PLT2M-M20				—						
PLT2M-M30				Heat-Resistant						
PLT2S-C	1.88 (47.8)	7.4 (188)	0.19 (4.8)	50 (222)		Polypropylene	Natural	—	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT2S-C0							Black	UV-Resistant, Weather-Resistant		
PLT2S-C00										
PLT2S-C186	1.85 (47)	7.3 (186)		30 (133)		Dark Blue	Chemical-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, STS2, STH2	
PLT2S-C2	1.88 (47.8)	7.4 (188)		50 (222)	Nylon 6.6	Red	—			
PLT2S-C20						Black				
PLT2S-C3						Orange				
PLT2S-C4Y						Yellow				
PLT2S-C5						Green				
PLT2S-C6120	1.88 (48)	7.4 (188)		150 (668)	Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	
PLT2S-C702Y					ECTFE	Maroon	Heat-Resistant, UV- Resistant, Weather- Resistant			
PLT2S-C71					PEEK	Translucent Brown	Chemical-Resistant, High Heat-Resistant, Radiation-Resistant			
PLT2S-C76	1.88 (48)	7.4 (188)	0.19 (4.8)	50 (222)	ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLT2S-C8	1.88 (47.8)	7.4 (188)	0.19 (4.8)	50 (222)	Nylon 6.6	Gray	—	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT2S-C96A	1.85 (47)	7.3 (186)				Blue	Antimicrobial	GTS-E, GS2B-E, GTH-E, GS4H-E, STS2, STH2	
PLT2S-M	1.88 (47.8)	30 (133)				Polypropylene	Natural	—	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT2S-M0				Black	UV-Resistant, Weather-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2		
PLT2S-M00					Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT2S-M100	1.88 (48)			50 (222)	Nylon 6.6		Green	Chemical-Resistant	1000
PLT2S-M109		Red				—			
PLT2S-M20	Black								
PLT2S-M3	Orange								
PLT2S-M300	1.88 (47.8)	50 (222)		Nylon 6.6	Black	Heat-Resistant, UV- Resistant, Weather- Resistant	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2		
PLT2S-M4Y					Yellow	—			
PLT2S-M6120	1.88 (48)	150 (668)		PEEK	Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	
PLT2S-M702Y					ECTFE	Maroon	Heat-Resistant, UV- Resistant, Weather- Resistant		
PLT2S-M71					Translucent Brown	Chemical-Resistant, High Heat-Resistant, Radiation-Resistant			
PLT3H-L0	3 (76)	11.4 (290)		0.3 (7.6)	120 (534)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant	50
PLT3H-L186		11.1 (282)	60 (267)		Polypropylene	Dark Blue	Chemical-Resistant	GTH-E, GS4H-E, GS4EH-E, STH2, ST3EH	
PLT3H-L76		11.5 (292)	120 (534)		ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT3H-L96A		11.1 (282)			Nylon 6.6	Blue	Antimicrobial	250	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
PLT3H-TL0		11.4 (290)	50 (222)			Polypropylene	Black		
PLT3H-TL100					Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT3H-TL30			120 (534)		Nylon 6.6	Heat-Resistant			
PLT3H-TL76		ETFE			Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant			
PLT3I-C	3 (76)	11.4 (290)	0.145 (3.7)	40 (178)	Nylon 6.6	Natural	—	100	GTS-E, GS2B-E, PTS, PPTS, STS2

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLT3I-C0	3 (76)	11.4 (290)	0.145 (3.7)	40 (178)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, PTS, PPTS, STS2
PLT3I-M						Natural	—	1000	
PLT3I-M0						Black	UV-Resistant, Weather-Resistant		
PLT3I-M20							—		
PLT3I-M30							Heat-Resistant		
PLT3S-C		11.5 (292)	0.19 (4.8)	50 (222)	Polypropylene	Natural	—	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT3S-C186		11.5 (291)		30 (133)		Dark Blue	Chemical-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, STS2, STH2
PLT3S-C2		11.5 (292)		50 (222)	Nylon 6.6	Red	—	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT3S-C6120					Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLT3S-C702Y		11.6 (295)		ECTFE	Maroon	Heat-Resistant, UV- Resistant, Weather- Resistant			
PLT3S-C76				ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant			
PLT3S-C96A		11.5 (291)		Nylon 6.6	30 (133)	Blue	Antimicrobial	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, STS2, STH5
PLT3S-M		Natural				—	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2		
PLT3S-M0		Black			UV-Resistant, Weather-Resistant				
PLT3S-M00					Chemical-Resistant, UV-Resistant, Weather-Resistant	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2			
PLT3S-M100		50 (222)			Polypropylene		Green	Chemical-Resistant	1000
PLT3S-M109									
PLT3S-M2		11.5 (292)			Nylon 6.6	Red	—	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT3S-M20	Black								
PLT3S-M3	Orange								
PLT3S-M30	Black					Heat-Resistant			
PLT3S-M300		Heat-Resistant, UV- Resistant, Weather- Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2					
PLT3S-M6120		Chemical-Resistant, UV-Resistant, Weather-Resistant							
PLT3S-M702Y	3 (76)	11.6 (295)	0.19 (4.8)	50 (222)	ECTFE	Maroon	Heat-Resistant, UV- Resistant, Weather- Resistant	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)					
Part Number					Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLT3S-M76	3 (76)	11.6 (295)	0.19 (4.8)	50 (222)	ETFE	Aqua	Chemical-Resistant, UV-Resistant, Weather-Resistant	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLT4.5S-M	4.5 (114)	15.5 (394)			Nylon 6.6	Natural	-		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2
PLT4H-C	4 (102)	14.5 (368)	120 (534)	Black				UV-Resistant, Weather-Resistant	
PLT4H-C0				Natural		-	50	GTH-E, GS4H-E, GS4EH-E, STH2, ST3EH	
PLT4H-L		14.4 (366)	60 (267)	Polypropylene		Dark Blue		Chemical-Resistant	GTH-E, GS4H-E, GS4EH-E, STH2, ST3EH
PLT4H-L186				120 (534)	ETFE	Aqua		Chemical-Resistant, UV-Resistant, Weather-Resistant	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
PLT4H-L76		Nylon 6.6	Blue		Antimicrobial	GTH-E, GS4H-E, GS4EH-E, STH2, ST3EH			
PLT4H-L96A			Natural		-	250	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH		
PLT4H-TL			4.11 (104.5)		14.5 (368)			0.3 (7.6)	50 (222)
PLT4H-TL0		Nylon 6.6		Black					
PLT4H-TL0/147	Heat-Resistant, UV- Resistant, Weather- Resistant								
PLT4H-TL00	Nylon 612								
PLT4H-TL100		120 (534)	Nylon 6.6	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4H-TL30	Nylon 6.6				Black	Heat-Resistant			
PLT4H-TL300		Nylon 612	Ivory	Flame-Retardant					
PLT4H-TL6120	Nylon 6.6			Black	Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4H-TL69		Nylon 6.6	Black		Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4I-C	Nylon 6.6			Black	Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4I-C0		Nylon 6.6	Black		Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4I-M	Nylon 6.6			Black	Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4I-M0		Nylon 6.6	Black		Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4I-M30	Nylon 6.6			Black	Chemical-Resistant, UV-Resistant, Weather-Resistant				
PLT4S-C		4 (102)	14.5 (368)		0.19 (4.8)	50 (222)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant
PLT4S-C0	4 (102)	14.5 (368)	0.19 (4.8)	50 (222)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)						
Part Number					Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With	
PLT4S-C00	4 (102)	14.5 (368)	0.19 (4.8)	50 (222)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	
PLT4S-C186		14.4 (366)		30 (133)	Polypropylene	Dark Blue	Chemical-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, STS2, STH2	
PLT4S-C2		14.5 (368)		50 (222)	Nylon 6.6	Red	-		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	
PLT4S-C4Y						Yellow				
PLT4S-C6120					Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	
PLT4S-C76		ETFE			Aqua					
PLT4S-C96A		14.4 (366)			Nylon 6.6	Blue	Antimicrobial		GTS-E, GS2B-E, GTH-E, GS4H-E, ST2S, STH2	
PLT4S-M		14.5 (368)		Nylon 6.6		Natural	-	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2		
PLT4S-M0						Black	UV-Resistant, Weather-Resistant			
PLT4S-M00				Polypropylene	Chemical-Resistant, UV-Resistant, Weather-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2			
PLT4S-M100						Green		Chemical-Resistant		
PLT4S-M109					50 (222)	Nylon 6.6	Red	-	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2	
PLT4S-M2				Black						
PLT4S-M20				Orange						
PLT4S-M3				Black		Heat-Resistant, UV- Resistant, Weather- Resistant	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2			
PLT4S-M300				Yellow		-				
PLT4S-M4Y						Nylon 612	Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLT4S-M6120				Ivory	Flame-Retardant					
PLT4S-M69				5 (127)	20.1 (511)	0.5 (12.7)	250 (1112)	Nylon 6.6	Natural	-
PLT5EH-C		Black	UV-Resistant, Weather-Resistant							
PLT5EH-C0									19.8 (503)	
PLT5EH-NB-C0	20.1 (511)	0.35 (8.9)	175 (778)		Natural	-	100		GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT5EH-Q0	17.7 (450)				Black	UV-Resistant, Weather-Resistant				
PLT5H-C	17.7 (450)					Heat-Resistant				
PLT5H-C0	5 (127)	17.7 (450)	0.35 (8.9)	175 (778)	Nylon 6.6	Natural	-	50	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT5H-C30										
PLT5H-L	5 (127)	17.7 (450)	0.35 (8.9)	175 (778)	Nylon 6.6	Natural	-	50	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With		
PLT5H-L0	5 (127)	17.7 (450)	0.35 (8.9)	175 (778)	Nylon 6.6	Black	UV-Resistant, Weather-Resistant	50	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH		
PLT5S-C		17.5 (445)	0.19 (4.8)	50 (222)		Natural	—	100	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2		
PLT5S-C0						Black	UV-Resistant, Weather-Resistant	1000			
PLT5S-M						Natural	—				
PLT5S-M0						Black	UV-Resistant, Weather-Resistant				
PLT5S-M30							Heat-Resistant				
PLT6EH-C0	6 (152.4)	22.2 (564)	0.5 (12.7)	250 (1112)		Black	UV-Resistant, Weather-Resistant	100	GS4EH-E, ST3EH		
PLT6EH-Q0							25				
PLT6H-C	6 (152)	20.9 (530)	0.35 (8.9)	175 (778)		Natural	—	100	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH		
PLT6H-C0						Black	UV-Resistant, Weather-Resistant				
PLT6H-C30							Heat-Resistant				
PLT6H-L						Natural	—	50			
PLT6H-L0		21.9 (556)	0.3 (7.6)	120 (534)		Black	UV-Resistant, Weather-Resistant				
PLT6LH-C						Natural	—	100			
PLT6LH-C0						Black	UV-Resistant, Weather-Resistant				
PLT6LH-L						Natural	—	50			
PLT6LH-L0						Black	UV-Resistant, Weather-Resistant				
PLT7LH-C		7 (178)		24.7 (627)			Nylon 612	Natural		—	100
PLT7LH-C0	Black							UV-Resistant, Weather-Resistant			
PLT7LH-C30								Heat-Resistant			
PLT7LH-C6120	Nylon 6.6						Black	Chemical-Resistant, UV-Resistant, Weather-Resistant	50		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLT7LH-L							Natural	—			
PLT7LH-L0							Black	UV-Resistant, Weather-Resistant	100		
PLT8EH-C0	8 (203.2)	28.3 (719)	0.5 (12.7)	250 (1112)		Natural	—	50			
PLT8H-C						Black	UV-Resistant, Weather-Resistant				
PLT8H-C0	9 (229)	30.6 (779)	0.35 (8.9)	175 (778)		Black	Heat-Resistant				
PLT8H-C30											
PLT8H-L						Natural	—	50			
PLT8H-L0						Black	UV-Resistant, Weather-Resistant				
PLT8H-Q0	8 (203.2)							25	GTH-E, GS4H-E, GS4EH-E, PTH		
PLT8LH-C	8 (203)	27.6 (701)	0.3 (7.6)	120 (534)	Nylon 6.6	Natural	—	100	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH		

Cabinets,
Thermal
Mgmt,
Racks &
Enclosures

Fiber Optic
Systems

Grounding
& Bonding

Power, Env,
Security &
Connectivity
Hardware

Safety &
Security

Signs,
Labels
& ID

Wire
Routing,
Mgmt &
Protection

Wire
Termination

Part
Number
Index

Pan-Ty® Locking Cable Tie (continued)

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With	
PLT8LH-C0	8 (203)	27.6 (701)			Nylon 6.6	Black	UV-Resistant, Weather-Resistant	100	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT8LH-C6120					Nylon 612		Chemical-Resistant, UV-Resistant, Weather-Resistant		GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	
PLT9LH-C	9 (229)	30.5 (775)	0.3 (7.6)	120 (534)	Nylon 6.6	Natural	–	100	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH	
PLT9LH-C0						Black	UV-Resistant, Weather-Resistant			
PLT9LH-C30							Heat-Resistant			
PLT9LH-C300						Black	Heat-Resistant, UV- Resistant, Weather- Resistant	50		
PLT9LH-L						Natural	–			
PLT9LH-L0						Black	UV-Resistant, Weather-Resistant			

Full product portfolio and solutions at panduit.com

