

Pan-Ty® Locking Double Clamp Tie with Spacer

- Impact Modified, Heat Stabilized, Weather Resistant Nylon 6.6 material has greater resistance to damage caused by ultraviolet light – indoor or outdoor use. For high temperature applications up to 239°F (115°C).
- A fast and economical method to secure and separate two bundles
- Efficient design allows a single cable tie to securely support multiple bundles
- Installs easily by hand – second loop can be installed with Panduit® cable tie installation tools



PLDC1.5EH-C350



PLDC2.5EH-C350

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Body Thickness In. (mm)	Min. Loop Tensile Strength lb/ft (N)	For Use With	Color	Resistance Properties	Std. Pkg. Qty.
PLDC1.5EH-C350	1.3 (33)	13.1 (333)	0.5 (12.7)	0.055 (1.4)	150 (667)	GTH-E, GS4EH-E	Black	Heat-Stabilized, Weather-Resistant	100
PLDC1.5EH-L350									50
PLDC2.5EH-C350	2.3 (58)	19.2 (489)							100
PLDC2.5EH-L350									50

Pan-Ty® Locking Wing Push Mount Cable Tie

- For high temperature applications up to 185°F (85°C) – indoor use
- Heat stabilized material option available for high temperature applications up to 239°F (115°C) - indoor use
- Cable tie, mount, and fastener in a single part
- Used to attach bundles to another surface such as a flat panel
- Anchor is easily pressed into a pre-formed hole and locks in place
- Wings provide constant tension for a stable, secure, and rattle-free installation
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



PLWP1.5I-D



PLWP1M-D30

Part Number	Overall Length In. (mm)	Body Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLWP1.5I-D	6 (152)	0.135 (3.4)	1.25 (31.8)	40 (178)	Nylon 6.6	Natural	–	500	GTS-E, GS2B-E, PTS, PPTS, STS2
PLWP1M-D	4.3 (109)	0.098 (2.5)	0.87 (22.1)	18 (80)		Black	Heat-Resistant		
PLWP1M-D30			0.87 (22)						
PLWP1SB-D	5.2 (132)	0.19 (4.8)	1 (25.4)	50 (222)	Nylon 6.6	Natural	–	500	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLWP1S-D	5.2 (132)	0.19 (4.8)	1 (25.4)	50 (222)		Natural	–		

Pan-Ty® Locking Wing Push Mount Cable Tie (continued)

Part Number	Overall Length In. (mm)	Body Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLWP1S-D30	5.2 (132)	0.19 (4.8)	1 (25)	50 (222)	Nylon 6.6	Black	Heat-Resistant	500	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLWP2S-D	7.8 (198)		1.75 (44.5)			Natural	-		

Pan-Ty® Releasable Wing Push Mount Tie

- All-in-one wing push mount design to attach bundles to another surface
- Extended release tab permits easy release and re-use where changes are anticipated during development, production or servicing in the field
- Anchor is easily pressed into a pre-formed hole and locks in place
- Wings provide constant tension for a stable, secure, and rattle-free installation
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- Extended release tab permits easy release and re-use where changes are anticipated during development, production, or servicing in the field
- UV-Resistant before Weather-Resistant option offers great resistance to damage caused by ultraviolet light - indoor/outdoor use for temperatures up to 185°F (85°C)



PRWP1.5S-D



PRWP1.5S-D0

Part Number	Overall Length In. (mm)	Body Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PRWP1.5S-D	6.8 (173)	0.19 (4.8)	1.5 (38.1)	50 (222)	Nylon 6.6	Natural	None	500	Hand Install Only
PRWP1.5S-D0						Black	UV-Resistant, Weather-Resistant		



Explore our Network Infrastructure catalog at panduit.com/catalogs

Pan-Ty® Locking Push Mount Tie

- Natural nylon material for indoor use with temperature applications up to 185°F (85°C)
- UV and weather-resistant material, suitable for indoor and outdoor installations with continuous use temperatures up to 185°F (85°C)
- Wingless design allows tie to be used in confined spaces
- Cable tie, mount, and fastener in a single part
- Economical push mount ties are used to attach bundles to another surface such as a flat panel
- Anchor is easily pressed into a pre-formed hole and locks in place
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation



PLP1S-M



PLP2S-M0

Part Number	Overall Length In. (mm)	Body Width In. (mm)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Material	Color	Resistance Properties	Std. Pkg. Qty.	For Use With
PLP1S-M	5.3 (135)	0.19 (4.8)	1 (25.4)	50 (222)	Nylon 6.6	Natural	—	1000	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2
PLP2S-M	7.9 (200)		1.75 (44.5)			Black	UV-Resistant, Weather-Resistant		
PLP2S-M0									

Pan-Ty® Write-On Flag Cable Tie

- Nylon 6.6 material for general indoor applications in temperatures up to 185°F (85°C)
- Multiple color options. Consult panduit.com for available options
- Flag marker ties are used to simultaneously fasten and identify bundles
- Can be marked with marker pens or computer printable labels
- Curved tip for easy to pick up from flat surfaces and faster initial threading during installation



PLF1M-C



PLF1MA-C



PLF1MA-M4Y

Part Number	Overall Length In. (mm)	Body Width In. (mm)	Body Thickness In. (mm)	Write-On Area (In.)	Max. Bundle Diameter In. (mm)	Min. Loop Tensile Strength lb/ft (N)	Color	Std. Pkg. Qty.	Std. Ctn. Qty.
PLF1MA-C	5.1 (130)	0.098 (2.5)	0.045 (1.1)	1.04W x 0.76H	0.87 (22.1)	18 (80)	Natural	100	1000
PLF1MA-M							1000	10000	
PLF1MA-M4Y				Yellow					
PLF1M-C	4.3 (109)						Natural	100	1000
PLF1M-M								1000	25000