

Pan-Ty® Wide Strap Cable Tie

- The wide, thin strap is more flexible, making it ideal for installations under high vibration conditions
- Impact Modified, Heat-Resistant, UV-Resistant, Weather-Resistant for indoor/outdoor heavy duty applications with temperatures up to 239°F (115°C)



PLWS2EH-TL350

Part Number	Max. Bundle Diameter (In.)
PLWS2EH-TL350	2.25
PLWS3EH-TL350	3.25
PLWS4EH-TL350	4.13

Pan-Ty® Double Loop Cable Tie

- Reduces part number inventory by managing multiple bundle sizes with a single cable tie
- UV and weather-resistant material, suitable for indoor and outdoor installations with continuous use temperatures up to 185°F (85°C)
- Heat stabilized material, suitable for high temperature indoor applications up to 239°F (115°C)



PLB2S-C0

Part Number	Max. Bundle Diameter In. (mm)	Overall Length In. (mm)	Body Width In. (mm)	Body Thickness In. (mm)	Min. Loop Tensile Strength lb/ft (N)	For Use With	Color	Resistance Properties	Std. Pkg. Qty.	Std. Ctn. Qty.
PLB2S-C0	1.8 (45.7)	7.6 (193)	0.19 (4.8)	0.052 (1.3)	50 (222)	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2	Black	UV-Resistant, Weather-Resistant	100	1000
PLB2S-M0								Heat-Resistant	1000	10000
PLB2S-M30										
PLB3S-M0	3 (76.2)	11.8 (300)						UV-Resistant, Weather-Resistant	1000	10000
PLB3S-M30								Heat-Resistant		
PLB4H-TL0	3.6 (91)	14.7 (373)	0.3 (7.6)	0.075 (1.9)	120 (534)	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH		UV-Resistant, Weather-Resistant	250	2500
PLB4S-M0	4 (104.1)	14.8 (376)	0.19 (4.8)	0.052 (1.3)	50 (222)	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH, PPTS, STS2, STH2			1000	5000