

ROHRflex PA 6-L

ROHRflex corrugated plastic tubings


Protective all-plastic tubing, internally and externally corrugated, fine or coarse profile, fire protection, economical, HB (UL 94), ECE-R 118.03 (orange)

Temperature: -25°C ... +120°C

Material: PA 6 plastics

CHARACTERISTICS:

- Properties: air- and liquid-tight
- oil resistant up to + 80°C
- benzine resistant
- widely resistant to acid and solvents
- free of silicone, cadmium, halogen
- flame retardant
- UV-resistant



APPLICATIONS:

- Application: machine and plant constructions / automotive / shipbuilding / automation / electrical installations



** VDE valid for OD 15,8 – 54,5 mm

FLEXA No.	Colour	OD [mm]	Profile	ID [mm]	OD [mm]	BR stat. [mm]	BR dyn. [mm]	Weight [kg/m]	PU [m]
10261202006	Black	10,0	fine	6,5	10,0	13	35	0,020	50
10261202010	Black	13,0	fine	10,0	13,0	20	45	0,024	50
10261202012	Black	15,8	fine	12,0	15,8	35	55	0,034	50
10261202014	Black	18,5	fine	14,3	18,2	40	65	0,050	50
10261202016	Black	21,2	fine	16,5	21,2	45	75	0,056	50
10261202023	Black	28,5	fine	22	28,5	55	100	0,100	50
10261202029	Black	34,5	fine	29,0	34,5	65	120	0,122	25
10261202036	Black	42,5	fine	35,5	42,5	90	150	0,145	25
10261202048	Black	54,5	fine	48,0	54,5	100	190	0,225	25
10261232016	Black	21,2	coarse	15,5	21,2	45	75	0,056	50
10261232023	Black	28,5	coarse	22	28,5	55	100	0,090	50
10261232029	Black	34,5	coarse	27,5	34,5	65	120	0,120	25
10261232036	Black	42,5	coarse	35,5	42,5	90	150	0,165	25
10261232048	Black	54,5	coarse	47,0	54,5	100	190	0,225	25
10261201006	Grey	10,0	fine	6,5	10,0	13	35	0,020	50
10261201010	Grey	13,0	fine	10,0	13,0	20	45	0,024	50
10261201012	Grey	15,8	fine	12,0	15,8	35	55	0,034	50
10261201014	Grey	18,5	fine	14,3	18,2	40	65	0,050	50
10261201016	Grey	21,2	fine	16,5	21,2	45	75	0,056	50
10261201023	Grey	28,5	fine	23,0	28,5	55	100	0,100	50
10261231016	Grey	21,2	coarse	15,5	21,2	45	75	0,056	50
10261231023	Grey	28,5	coarse	22,0	28,5	55	100	0,090	50



FLEXA No.	Colour	OD [mm]	Profile	ID [mm]	OD [mm]	BR stat. [mm]	BR dyn. [mm]	Weight [kg/m]	PU [m]
10261231029	Grey	34,5	coarse	27,5	34,5	65	120	0,120	25
10261231036	Grey	42,5	coarse	35,5	42,5	90	150	0,165	25
10261231048	Grey	54,5	coarse	47,0	54,5	100	190	0,225	25
10261209006	Orange	10,0	fine	6,5	10,0	13	35	0,020	50
10261209010	Orange	13,0	fine	10,0	13,0	20	45	0,024	50
10261209012	Orange	15,8	fine	12,0	15,8	35	55	0,034	50
10261209014	Orange	18,5	fine	14,3	18,2	40	65	0,050	50
10261209016	Orange	21,2	fine	16,5	21,2	45	75	0,056	50
10261239016	Orange	21,2	coarse	15,5	21,2	45	75	0,056	50
10261239023	Orange	28,5	coarse	22,0	28,5	55	100	0,090	50
10261239029	Orange	34,5	coarse	27,5	34,5	65	120	0,120	25
10261239036	Orange	42,5	coarse	35,5	42,5	90	150	0,165	25
10261239048	Orange	54,5	coarse	47,0	54,5	100	190	0,225	25

** VDE valid for OD 15,8 – 54,5 mm

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.